






Technical DATA SHEET

FLOORPAN PRIME

8 MM - CLASS 32 - AC4

THICKNESS	mm	8	EN 13329+A1
WIDTH	mm	193	EN 13329+A1
LENGHT	mm	1205	EN 13329+A1
SURFACE		Impact	
EUROPEAN STANDARD	-	  	EN 13329
PACKAGE DETAILS			
PIECE	8 piece / 1 package		
M ²	1,86 m ²		
KG	14 kg		
PALLET DETAILS			
PIECE	60 package / 1 pallet		
M ²	111,66 m ²		
KG	840 kg		
CLASS	-	32	EN 13329+A1
ABRASION RESISTANCE	-	AC4	EN 13329+A1
THICKNESS SWELLING	%	≤18	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	EN 13329+A1
	LARGE BALL	mm	
WARRANTY DOMESTIC / COMMERCIAL	Years	15/10	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438-2_5
SURCAFE SOUNDNESS	N/mm ²	≥1.25	EN 13329+A1
LOCK STRENGTH	LENGHT	kN/m	ISO 24334
	WIDTH	kN/m	
EFFECT OF A CASTOR CHAIR	25.000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A1
HEIGHT DIFFIRENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A1
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C _s S1	EN 9239-1
FORMALDEHYDE RELEASE	mg/m ² h	≤3,5 (E1)	EN 12460-3
SLIP RESISTANCE	Class	DS	EN 13893:2003
IMPACT SOUND REDUCTION	dB	14	EN ISO 10140-3
THERMAL RESISTANCE	(m ² K)/W	0,05	EN 12664:2009

