



DryPlus® Masonry Waterproofer

- Smooth, Decorative Interior/Exterior Flat Finish
- 10 Year Guarantee*
- Withstands 12 PSI of Water Pressure
- Mildew Resistant Film
- 100% Styrene Acrylic
- Sprayable! Saves Application Time

No. 875 White

No. 876 Basement Gray



2 Coats Required
for Optimal Durability



Spread Rate:
Rough 75-100 Sq. Ft.
Smooth 100-125 Sq. Ft.



Dry Time:
1 Hr. Dry to Touch
4 Hr. Recoat



Soap & Water
Clean-Up

READY TO USE OR ADD TINTING COLORANTS

WHERE TO USE

Walls subject to hydrostatic pressure. Ideal for above or below grade Basement Walls, Retaining Walls, Garage Walls, Masonry Walls, Cinder Blocks, Stucco, Brick, Foundations and Landscape Walls. Apply to dry or slightly damp surfaces. **Not for use on floors or walls with active water leaks.**

PREPARATION

(Proper surface preparation is required.) New or Unpainted Surfaces: New concrete must cure for a minimum of 30 days. Test for loose, flaking concrete by pressing a piece of masking or transparent tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be painted. If the existing concrete is removed, the loose concrete should be removed down to a sound substrate. **For below grade application:** All holes or cracks must be properly patched with a fast setting hydraulic cement. **For above grade application:** Remove mildew stains with a mildew stain removing product. All surfaces must be clean and free of dirt, dust, efflorescence and oil. Clean surface with a Concrete & Masonry Cleaner & Etcher. Follow all label instructions. **Previously Painted Surfaces:** BEHR DryPlus Masonry Waterproofer provides best results when applied to bare or untreated surfaces. PREVIOUSLY PAINTED SURFACES IN GOOD, REPAINTABLE CONDITION MAY BE PAINTED WITH BEHR NO. 875 or NO. 876, HOWEVER, BEHR WILL NOT GUARANTEE THE RESULTS. Test for loose, flaking paint by pressing a piece of masking or transparent tape at various places, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be painted. If the existing paint is removed, the loose paint should be removed down to a sound substrate by wire brushing or sanding. For Interior or Exterior application; remove deteriorated coating prior to application. Follow all preparation instructions under "New or Unpainted Surfaces" above.

*LIMITED WARRANTY

Behr Process Corporation warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for 10 years from the date of purchase. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED, VERTICAL SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2018 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. <100 g/L • REV. 6/18

APPLICATION

Stir well before use. Do not thin product. Use with adequate ventilation. Use product when air and surface temperature are 50-90°F (10-32°C). Apply to dry or slightly damp masonry walls. Wipe off any visible moisture with a dry cloth before painting. Apply using a high quality 1/2-3/4" nap roller, 4" nylon/ polyester brush or an airless sprayer capable of delivering 0.5 GPM or greater using a .023-.025" spray tip. **Two coats minimum are required:** **First Coat:** Using a brush or roller, work the waterproofer onto the surface until all pores or voids are covered. **Second Coat:** Using a brush or roller, cover the entire surface. Properly fill any voids left after the first coat. Additional spot application may be needed depending on the porosity of the surface. **Important: If leaking is still present after two coats, it indicates that voids or pinholes are still open. Re-apply product to these areas. DO NOT thin product or apply at a greater spread rate.**

DRY TIME

Low temperatures or high humidity conditions will affect drying time. Full cure should be reached in 7-14 days.

DISPOSAL

Properly dispose of all soiled rags and **protect unused product from freezing.** For disposal of empty containers and unused product contact your household refuse collection service.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION IRRITANT MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**