


FEATURES

- Solid brass construction for durability and reliability
- Single-function Rain showerhead
- Air-induced Spray Technology
- Optimized sprayface for maximum performance
- 2.5 gpm (9.5 lpm) flow rate
- 1/2" NPT connection
- Complements the Vir Stil collection

CODES/STANDARDS APPLICABLE

- Specified model meets or exceeds the following:
- ASME A112.18.1/CSA B125.1
 - Energy Policy Act of 1992

P21671



SPECIFIED MODEL					
Model	Description	Finishes			
P21671-00	Vir Stil Raindome	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver	<input type="checkbox"/> AG Brushed Nickel	<input type="checkbox"/> LB Bronze
Required Arm Options					
P21520-00	3" Ceiling-mount shower arm	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver	<input type="checkbox"/> AG Brushed Nickel	<input type="checkbox"/> LB Bronze
P21521-00	6" Ceiling-mount shower arm	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver	<input type="checkbox"/> AG Brushed Nickel	<input type="checkbox"/> LB Bronze
P21522-00	12" Ceiling-mount shower arm	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver	<input type="checkbox"/> AG Brushed Nickel	<input type="checkbox"/> LB Bronze
P21523-00	Wall-mount shower arm	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver	<input type="checkbox"/> AG Brushed Nickel	<input type="checkbox"/> LB Bronze

We reserve the right to make revisions without notice in the design of products or in packaging unless this right has specifically been waived at the time the order is accepted.