

GY 3000PW

HIDROLIMPIADORA A GASOLINA
PETROL HIGH PRESSURE WASHER



Ref.: GY3000PW

ESPECIFICACIONES TÉCNICAS TECHNICAL SPECIFICATIONS

		GY 3000PW	
MOTOR ENGINE	Marca	Brand	GOODYEAR Licensed
	Tipo	Type	OHV
	Cilindrada (cc)	Displacement (cc)	196
	Potencia Nominal (Kw / hp)	Rated Power (Kw / hp)	4.1 kW / 5.6 hp
	Potencia máxima (kw / hp) 3600rpm	Max. Power (Kw / hp) 3600rpm	4.8 kW / 6.5 hp
	Arranque	Starter	Manual
	Encendido	Encendido	Magneto transistorizado / Transistorized magneto
Depósito de Combustible (l)	Petrol tank (l)	3.6	
BOMBA PUMP	Presión máx. Nominal (PSI - bar)	Rated max. Pressure (PSI - bar)	3000 PSI / 206 bar
	Caudal máximo (l/h)	Maximum flow (l/h)	570
	Maxima temperatura de agua (°C)	Max. Water temperature (° C)	60
	Tipo	Type	Axial en aluminio / Axial in aluminum
	Pistones	Pistons	3 en acero templado / 3 tempered steel
	Longitud manguera alta presión (m)	High pressure hose lenght (m)	8
	Depósito detergente (ml)	Detergent Tank (ml)	2000
ACCESORIOS ACCESSORIES	Lanza regulable	Regulable lance	No
	Boquilla turbo	Turbo nozzle	Si / Yes
	Filtro agua	Water filter	Si / Yes
	Depósito detergente	Soap deposit	Si / Yes
	Enrollador manguera	Hose reel	No
EMBALAJE PACKING	Dimensiones (mm)	Dimensions (mm)	560 x 530 x 625
	Container loads (20"/40"/40HQ)	Container load (20"/ 40"/ 40HQ)	168 / 338 / 451
	EAN	EAN	8434691105478
	Peso Neto / Bruto	NW / GW	32 / 35 Kg
OTRAS CARACTERÍSTICAS OTHER SPECIFICATIONS	Ruedas de transporte	Transport wheels	
	Autonomía aproximada 2,2h con 1 depósito	Approximate authonomy 2,2h with 1 fuel tank	
	5 boquillas INCLUIDAS (Jabon, 0°, 15°, 25°, 40°)	INCLUDED 5 Nozzles (Soap, 0. 15°, 25°, 40°)	

