



- Mechanical bimetal switch with Cadmium
- Sulfide photocell
- Delay feature prevents unwanted OFF switching
- Gray plastic housing
- 1/2"-14 NPSM threaded stem
- Washer gasket and locking nut included
- #18 AWG, 9" wire leads

Input Voltage Range(s)	120 VAC, 50/60 Hz
Activation Off	3 to 15 fc
Application Compatibilities	Fluorescent, HID, Incandescent
Color	Gray
Cover Color	Gray
Housing Material	Polycarbonate
Magnetic Ballast Range(s)	8.3 A, 1000 VA
Photo Control Switch Type	Mechanical Bimetal
Photocontrol Sensor Location	Side
RoHS Certification	X
Tungsten (NO)	15 A, 1800 W
UL Standard	UL 773
Warranty Period	2-Year limited
Wiring Option	Wire leads
Check Valve	False
Freeze protection	False
Operating Temperature Max (°F)	158
Operating Temperature Min (°F)	-40
Product Depth (mm)	39,7
Product Height (mm)	76,2
Product Width (mm)	39,7
UL Certification	UL
Unit Carton Length (in)	3
Unit Carton Width (in)	1,75
UV Resilient Outdoor Enclosure	False

Photocontrol Style	Stem Mount
Activation On	1 to 5 fc
CA Prop 65 Message	Please see the Warning @
Country Of Origin	<a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
	Mexico
Fail Mode	ON
Magnetic Ballast (NO)	8.3 A, 1000 VA
Material	Polycarbonate
Photocell Type	Cadmium Sulfide
Photocontrol Type	Thermal
Sensor Time Delay	30 sec to 90 sec
Tungsten Range(s)	15 A, 1800 W
Usage Environments	Outdoor
Wire Size Max	#18 AWG
Auto Start/Stop	False
DOE Compliant	False
Operating Temperature Max (°C)	70
Operating Temperature Min (°C)	-40
Product Depth (in)	1,563
Product Height (in)	3
Product Width (in)	1,563
Submersible	False
Unit Carton Height (in)	4,88
Unit Carton Weight (lb)	0,21
Units Per Pallet	2400



# Stem Mount Thermal Photocontrol 120 V

## Wiring Diagram

