

Features

- Robust steel tube frame
- Insulated tank to prevent sweating
- Large flush actuator plate opening can be removed for easy access to inner tank
- Adjustable height allows bowl to be set anywhere from 15" to 23" (381 to 584 mm) from floor
- Dual-flush actuator offers a choice of 0.8 or 1.6 gpf (3.0 or 6.0 lpf)
- Requires K-76395 Veil smart wall-hung toilet (sold separately)

Technology

- Dual-flush technology allows you to choose between a full or partial flush

Installation


- Durable steel frame carrier is installed on 2" x 6" studs behind the wall. See installation guide and installation video for more detailed information
- When installed per KOHLER installation instructions, the KOHLER in-wall tank and carrier system can support up to 880 lbs. without damage
- Supply line sold separately

Water Conservation & Rebates

- Eligible for consumer rebates in some municipalities

Required Products/Accessories

K-76395 Wall-hung compact elongated smart toilet bowl, dual-flush



ADA

CSA B651

OBC

Codes/Standards

ASME A112.6.2
ASME A112.19.14
ADA
ICC/ANSI A117.1
CSA B651
OBC

KOHLER® Intelligent Toilet and C3® Cleansing Seat Three-Year Limited Warranty

See website for detailed warranty information.



Veil®
In-wall tank and carrier for K-76395 Veil® wall-hung
smart toilet
K-18647

No image available.
This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Toilet type:	Wall-mount In-wall mount
Waste Outlet:	Wall
Flush type:	Gravity washdown
Water Consumption	
Full:	1.6 gpf (6 lpf)

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.