

- Strong wet tack
- Excellent slip for positioning
- Great for pasting machines

**Dynamite® 785 Strippable Heavy Duty Clear Wallcovering Adhesive** is a versatile adhesive formulated to hang all types of wall-coverings from lightweight paper to heavyweight vinyls. An ideal adhesive for jobs that require future strippability. It is formulated to allow for future removal of fabric-backed vinyl wallcoverings from unprimed drywall without damage to the drywall surface. It is also the perfect choice for hanging wallcoverings such as fabric, strings, grasscloth and other natural materials.\*

\*FABRICS, FOILS, STRINGS, GRASSCLOTH AND SILK – When hanging delicate wallcoverings, special care must be taken in keeping the adhesive off the face of the wallcovering as it may cause permanent discoloration. It is recommended that a sample of the selected wallcovering be tested for degree of stain resistance prior to the installation. Some wallcovering can be stained by water alone.

**SURFACE PREPARATION:** Surface must be clean and free of oil, dust, dirt, grease, mildew, and other foreign matter. For best results, use Dynamite All-Purpose Cleaner to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in wall with Dynamite Non-Shrink Spackling prior to priming.

**Plaster** – New plaster must age at least 30 days before hanging wallcovering. Prime with Dynamite 221 or 222.

**Drywall** – New drywall must be wiped down with a damp cloth to remove dirt and dust. Prime with Dynamite 221 or 222.

**Other Porous Surfaces** – Walls must be clean, dry, smooth and structurally sound. Prime with Dynamite 221 or 222.

**Glossy Surfaces** – Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica®, glass or plastic should be primed with Dynamite 221, 222 or 235.

**Commercial Grade Type II & III** – Prime with Dynamite 235 when hanging heavy-weight commercial-grade papers.

**Strippability** – No primer is needed when hanging strippable, fabric-backed vinyl wallcoverings. Adhesive and primer (if used) must be completely cured prior to stripping. DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS IT IS PRIMED WITH A DYNAMITE ACRYLIC PRIMER.

**APPLICATION:** Mix well before using to ensure even consistency. For lightweight wallcoverings, thin as needed, up to 1 pint of water per gallon. Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to manufacturer's instructions. IMMEDIATELY remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. **Hang wallcovering according to manufacturer's instructions.**

**COVERAGE:** Five gallons of adhesive will hang up to 40 single rolls. (1400 sq. ft./5 gal.). Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions and method of application.

**PRECAUTIONS:** **Strippable Heavy Duty Clear Wallcovering Adhesive** should be stored at temperatures between 40 °F and 100 °F. PROTECT FROM FREEZING. For longest life, store in controlled environment, 55 °F-80 °F. Do not store in direct sunlight. Do not store/warehouse product below 32 °F for extended periods of time. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers. Do not use in drinking water or food systems. Keep container closed when not in use.

**QUALITY PROMISE:** Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7785-3-20	1 gal.	7.625" x 7.625" x 7.8125"	1 gal. / 3.79 L	10 lbs.	4/case	027134778537
7785-3-30	5 gal.	12.6" x 12" x 14.78"	5 g / 18.9 L	47 lbs.	1 ea.	027134778544