

Roof & Foundation Coating Liquid Asphalt Coating

- Weatherproofs roof and masonry surfaces
- Renews worn roof surfaces
- Great for foundations
- Odorless, water cleanup

Black Jack® Roof & Foundation Coating is a liquid applied, asphalt based coating. It is designed to penetrate and restore worn roof surfaces, foundation block walls, above or below grade and other masonry roof surfaces. Coating will weatherproof and help protect surfaces. This product is ideal to use as a base coat for reflective coatings. Can also be used to seal and protect underground wood footings and metal surfaces. Dries black in color.

PREP THE AREA: Remove all dust, dirt, and debris. Patch all cracks or seams with Black Jack Roof Cement. Remove all rust or loose paint from metal surfaces. May be applied to slightly damp surfaces, but do not apply to wet surfaces or if rain is expected within 24 hours. On foundations apply only over cured concrete and masonry. Product can be coated with a reflective coating 7 days after initial application.

HOW TO APPLY: Use brush or paint roller to spread across surface.

COVERAGE RATE: This 5-gallon pail covers 350 sq.ft., per coat, over masonry and roof surfaces, depending on texture and porosity of surface. Two coats are recommended for best results.

CLEAN UP: Water cleanup when wet, or mineral spirits when dry.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use on EPDM, Hypalon or PVC surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first. Do not use in drinking water or food systems. Do not allow product to freeze.

LIMITED WARRANTY: Gardner-Gibson warrants product to be free of material defects for a period of 3 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6190-9-34	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	8.5 lbs.	6/case	027134619014
6190-9-30	5 gal.	12" x 12" x 14.75"	4.75 gal. / 18 L	42.5 lbs.	1 ea.	027134619052